



Setup Instruction

For Secure Comfort Application



Wifi/Smart Home Compatible

FOR SMART HOME OR AUTOMATIC TIMER USE, THIS FEATURE MUST BE ENABLED ON THE BLANKET CONTROLLER.

To activate this feature:

1. Turn the controller off.
2. While off, press and hold the “PREHEAT” key for approximately 2 seconds until the display blinks “AO” for 20 setting controllers, or the preheat LED blinks once for 5 setting controllers.
3. Release the “PREHEAT” button and allow the display or LED to turn off.
4. The controller should now be in automatic mode.
5. To test, turn controller on and allow the display/LED to dim. Do NOT turn the controller off using the power switch. Disconnect the powercord from wall outlet, wait 5 seconds, then plug the power cord back in the wall outlet. The controller should power on, perform a powerup test, then remain operating at the last setting used during previous operation.

To disable this feature:

1. Turn the controller off.
2. While off, press and hold the “PREHEAT” key for approximately 2 seconds until the display blinks “OF” for a 20 setting controller, or the preheat LED blinks twice for a 5 setting controller.
3. Release the “Preheat” button and allow the display or LED to turn off.
4. The controller should now be in normal operation mode.
5. To test, turn controller on and allow the display/LED to dim. Do NOT turn the controller off using the power switch. Disconnect the powercord from wall outlet, wait 5 seconds, then plug the power cord back in the wall outlet. The controller should only perform a power up test, then shut off.

Copyright ©2023 E&E Co. Ltd., Inc. All rights reserved.

Terms of Service